

VISCOCER[®] 1017

产品描述

EINECS: 聚合物

VISCOCER[®] 1017 是一款氧化聚乙烯蜡。

物性	单位	目标值
外观	-	白色粉末
密度 (23°C)	g/cm ³	0.97
熔点 (DSC)	°C	116
酸值	mg KOH/g	17
粘度 (140°C)	mPa*s	600

主要应用领域

VISCOCER[®] 1017 用于不同类型的技术应用，例如纺织品和脱模剂用水基蜡乳液的制造。VISCOCER[®] 1017 在塑料里面作为脱模剂和润滑剂使用。

包装

PE袋 20 kg/包
1吨/托盘

储藏

产品必须在室温下干燥储存。小心阳光和热量。
稳定至少2年，从交付之日起。

危险

本产品不需要按照CLP/GHS指南进行标识。进一步安全相关数据见安全数据表。

生态学和毒理学特性

该产品是水不溶物。进一步信息见材料安全数据表。

食物法例下的地位

产品符合各国立法要求。更多详情请洽询。

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.

version 3.0 10.05.2017