

LUCRCHEM PEG 400

液体聚乙二醇(PEG)用于不同工业应用

产品简介

LUCRACHEM PEG 400 可作为增塑剂、保湿剂、助溶剂等多种工业应用中

技术参数

化学特性	聚乙二醇
离子型	非离子型
活性成份 [%]	100
形态	液体
颜色	无色
pH 值[1%的水溶液]	4-7
水中的混溶性	可溶

上述数据只是典型产品参数,需要更多信息,请参考相关产品说明书

产品特性及应用范围

LUCRACHEM PEG 400 可与水以任何比例混溶。它可以用于许多工业应用,如润滑油、印刷油墨、涂料、油漆、塑料生产、化妆品、制药工业等。因其性质多样,它也可以作为助溶剂、保湿剂、粘合剂、柔韧剂、增塑剂、反应模具(聚合工艺用)。

添加量和工艺

最优用量取决于各种参数(如应用,配方),必须由测试决定。

存储,处理与安全

保质期为24个月,从LEVACO仓库交货起,在原始封闭容器中,并在适当条件下储存。

有关安全、储存等方面的更多信息,请参阅我们公司网站 www.levaco.com 上提供的安全数据表



LUCRCHEM PEG 400

包装

该产品有以下包装规格:

1000kg/IBC

Disclaimer

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.

Edition: 01/04/2020

翁开尔(上海) 国际贸易有限公司电话:021-51691088上海市闰行区传真:021-52829830

中春路 1288 号 28 楼

201109 www.hjunkel-china.com

中国