

CERALENE[®] 2E 450/2000

产品描述

CAS-No.: 9002-88-4

CERALENE 2E 450/2000是一种非氧化聚乙烯蜡，细小颗粒。

物性	方法	单位	目标值
表观	目测	-	白色颗粒
粒径	ISO 3310-1	mm	< 5 % (0 – 0.45) 40 – 80 % (0.45 – 1.0) 20 – 40 % (1.0 – 1.6) < 5 % (1.6 – 2.0) < 1 % (2.0 – 2.8) 0 % (> 2.8)
滴点	PN-55/C-04020	°C	106
粘度(140°C)	PN-79/C 89404	mPa*s	130 – 190
针入度 (25°C)	PN-82/C-04161	mm*10 ⁻¹	≤ 2

主要应用领域

铝压铸机柱塞润滑剂。

包装

PE袋 20 kg/包
1吨/托盘

储藏

产品必须在室温下干燥储存。小心阳光和热量。稳定至少2年，从交付之日起。

危险

本产品不需要按照制备指南进行标识。进一步的安全相关数据见安全数据表。

生态学和毒理学特性

急性口服毒性LD50: > 2000 mg/kg(大鼠)
本品为水不溶物，对鱼类和细菌无不良影响。

食物法例下的地位

产品符合各国立法要求。更多详情请洽询。

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, can not be derived from this.