

3.1 合成磺酸钠

产品 **Sodium Sulfonate NA 440**

特性 **NA 440** 是一款油溶性的石油磺酸钠，应用于防锈剂，分散剂和乳化剂（防锈性能随分子量增大而增强，而乳化性能随之减弱）。由特殊的工艺制成，质量稳定。

技术资料	典型数值	规格最小	最大	
密度 15°C (g/cm ³)	: 1.01	0.98	1.03	DIN 51 757
活性成分 (wt.%)	: 61	60		ACL-028
矿物油(wt.%)	: 35	32	36	calculative
水 (wt.%)	: 3.5		5.0	DIN 51 777-1
无机盐 (wt.%)	: 0.4		0.5	ACL-035
平均分子量	: 440			calculative
闪点 (°C)	: min. 100			DIN EN ISO 2719
色度 (dil. 10%在白油中)	: 4			ACL-014

应用 推荐应用于金属加工液，纺织油，清洗剂，防锈剂，涂料，乳液，矿石浮选，印刷油墨，油漆等产品中。

存储 原装密封条件下可在 0°C 至 40°C 的室内温度下存放至少 12 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.