

# CERALENE® 1M

## 产品描述

CAS-No.: 9002-88-4

CERALENE® 1M 是一种低密度聚乙烯蜡，平均分子量为1500mw。

物性	单位	目标值
表观	-	白色微粒
密度(23°C)	g/cm <sup>3</sup>	0.92
滴点	°C	104
粘度(120°C)	mPa*s	260
针入度 (25°C)	mm*10 <sup>-1</sup>	3
酸值	mg KOH/g	0

## 主要应用领域

CERALENE® 1M 用于橡胶脱模剂、石蜡及其它聚合物的改性、PVC中的润滑剂、印刷工艺中溶剂型蜡膏的制备以及水基蜡乳液的制备。

## 包装

PE袋 20 kg/包  
1吨/托盘

## 储藏

产品必须在室温下干燥储存。小心阳光和热量。  
稳定至少2年，从交付之日起。

## 危险

本产品不需要按照制备指南进行标识。进一步的安全相关数据见安全数据表。

## 生态学和毒理学特性

急性口服毒性LD50: > 2000 mg/kg(大鼠)  
本品为水不溶物，对鱼类和细菌无不良影响。

## 食物法例下的地位

产品符合各国立法要求。更多详情请洽询。

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, can not be derived from this.