

产品 **Kusapour 85 (PPD)**

特性 **Kusapour 85** 是一款溶解在中性油中聚甲基丙烯酸酯类的粘性溶液，推荐用于润滑基础油的降凝剂使用。本产品在任何温度和浓度下均可完全溶于大多数石油产品。在成品润滑液中，本产品与其他常用添加剂相兼容。

技术数据

	典型数据	规格最小	规格最大		
外观	:	清晰，粘稠液体			
颜色	:	淡黄至琥珀色			
粘度 100°C (mm ² /s)	:	300	800	ASTM D445	
密度 25°C (g/cm ³)	:	0.91	0.88	0.94	ASTM D4052
闪点 COC (°C)	:	150		ASTM D92	

应用 **Kusapour 85** 除了用于工业用油和齿轮润滑剂外，还在单级和多级曲轴箱油中用作降凝剂。除了降低倾点外，本产品在一定的剪切条件下可以有效控制低温粘度。对于 I 类和 II 类油，添加量为 0.1 – 1.0%。最高混合温度为 90°C。

存储 该产品可以在密封的原始容器中于 + 5°C 至 + 40°C 的阴凉条件下安全地保存至少 12 个月。

The data contained herein serve as general information for our customers only and are not binding. The data contained herein have been collected to the best of our knowledge and do not constitute any advice or warranty to our customers for any specific application. It is up to our customer at their own risk to determine the suitability of each product for their individual purposes. The products are sold without any representation, warranty or guarantee either expressed or implied. Our liability is limited to the value of the supplied merchandise.